UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE INDEX.LEGEND
Concrete Monument. Previous ties missing. 2 SE corner SW4 SE4 : Set 12" x 30" lebar/cap 3" deep. 2 mid point on 1/2 mile.
Reason for corner certificate: There is no certificate for the corner on file with the recorder of the county in which the corner is located. The surveyor in responsible charge of the land surveying accepts a corner position which differs from that shown in the public records of the county in which the corner is located. The corner monument is replaced or modified in any way. The reference ties referred to in an existing public record are not correct. Double Mails Set The part of the county in which the corner is located. The reference ties referred to in an existing public record are not correct. The part of the county in which the corner is located. The corner monument is replaced or modified in any way. The reference ties referred to in an existing public record are not correct. The part of the county in which the corner is located. The corner monument is replaced or modified in any way. The reference ties referred to in an existing public record are not correct. The part of the county in which the corner is located. The corner monument is replaced or modified in any way. The reference ties referred to in an existing public record are not correct. The part of the corner is located. The corne
Field 8092 Entionee Souble nails Set on N Side of PP.
RR Spike.) 35585 On N Side of PP. Elia O L'b" x30" sebar/Lap 330 Utah Street.
X nails set on N side of PP. 3 All distances measured horizontal unless otherwise noted.
All distances measured horizontal unless otherwise noted. Certification: I hereby certify that this land surveying document was prepared, and the related survey work was performed by mean runder my direct personal supervision, and that I am a day licensed Professional Land Surveyor, under the laws of Direct No. 21980 Robert Hamis Lance Robert Hamis La